



## POLYX®-OIL CARE AND REPAIR PASTE

Ideal for the maintenance and repair of Polyx®-Oil surfaces!



3080 Clear



### PRODUCT DESCRIPTION

Clear oil-wax combination for repairing small damages in all wood surfaces treated with Polyx®-Oil. Osmo Polyx®-Oil Care and Repair Paste is based on natural plant oils and waxes. Suitable for wood; microporous surface. Simple application – without primer or intermediate sanding – this saves time and money. Resistant to wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots. The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

### RECOMMENDED USE

Osmo Polyx®-Oil Care and Repair Paste is ideal for the simple repair of small damages in all wood surfaces treated with Polyx®-Oil, such as furniture surfaces and worktops made of solid wood or laminated wood (e.g. kitchen worktops, tabletops, shelving etc.) in indoor areas. Also suitable for all wooden flooring, such as solid, plank, strip, OSB and cork flooring as well as stairs.

### INGREDIENTS

Based on natural plant oils and waxes (sunflower oil, soya oil, thistle oil, carnauba wax and candelilla wax), paraffin, siccatives (drying agents) and water-repellent additives. Dearomatized white spirit (benzene-free). EU limit value for this product (cat. A/i): 500 g/l VOC (2010). This product contains max. 500 g/l VOC. Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.88-0.95 g/cm<sup>3</sup>  
Viscosity: high viscosity – pasty  
Odour: faint/mild, after drying odourless  
Flash point: > 60°C acc. DIN EN ISO 2719

### STORAGE

Up to 2 years and longer if kept dry and tightly closed.

### SURFACE PREPARATION

Wood surface must be clean and dry. It is sufficient to wipe the surface with a lint-free cloth. Strongly contaminated surfaces can be cleaned with, for example, Osmo Spray Cleaner and rubbed dry. Sand small cracks, larger gaps or holes in wood and, if necessary, patch with Osmo Wood Filler.

### METHODS OF APPLICATION

With a lint-free cloth, apply thinly along the wood grain. Allow to dry for approx. 8-10 hours under good ventilation. If necessary, repeat the application as described above 2-3 times.

### DRYING TIME

Approx. 8-10 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

### COVERAGE

75 g covers 2-3 m<sup>2</sup> with one application on raw wood.

### NOTES

Oils enhance the natural colour of wood (permanent wet effect). Applying the product too generously and insufficient ventilation lead to delays in drying. If a higher gloss level is desired, after thoroughly drying apply Osmo Liquid Wax Cleaner thinly and polish when dry.



## CAUTION

Keep out of the reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

## DISPOSAL

Dispose of leftover product and packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

3080 Clear, Paste

## SIZES

75 g tube

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/18